

# FOAMING WAX

## Rinse Wax

Foaming Wax is a specially designed sealer wax which causes rinse water to plate out, leaving the surface of the vehicle smoother and free of water spots. Additionally, the sealer forms a barrier to protect the surface from road film and dust. Foaming Wax is not harmful to the environment, and eventually rinses off with either rain water, or additional washes. It may be reapplied after any wash with any type of detergent.

Use Foaming Wax wherever a better shine or a protectant is desired on cars, trucks, buses, tractors, trailers, heavy equipment, and even on aircraft.

In Tunnel Car Washes, pre-mix Foaming Wax at an 8:1 dilution ratio with water in a dedicated container, then apply 8 ounces of solution per car. For Drive-Thru or Gantry type Truck Washes, use the same dilution as for cars, but apply as needed for the larger vehicles. For Manual Spray, use a proportioning device capable of an 8:1 dilution as water passes through it, and lightly mist the vehicle after it has been thoroughly washed.

### SPECIFICATIONS FOR FOAMING WAX

Appearance.....	Clear, blue liquid
pH.....	7 ± .5
Specific Gravity.....	1.00
Percent Active.....	30-40%
Flash Point.....	None
Dilution.....	8:1 with water
Foam.....	High
Hardwater Tolerance.....	Excellent
Ammonia.....	Quaternary
Butyl.....	None
Phosphate.....	None
Storage Stability.....	Excellent, indefinite
USDA Registered?.....	No

HMIS RATINGS			
Health	<b>1</b>	Flammability	<b>2</b>
Reactivity	<b>0</b>	Personal Protection	<b>A</b>

PACKAGING
55 gallon, #5707-03P
30 gallon, #5707-05P
6 gallon pail, #5707-06P

