




CHEMISTRY • INNOVATION • SOLUTIONS

LIQUI-FIRE RXE

4-ADPA & Resin Stripper



Product Description

LIQUI-FIRE RXE is a self-emulsifying blend of solvents and penetrants that is used to remove hardened latex, isocyanates, resins, 4-ADPA, heavy petroleum, and polymers from stainless tanks, IBC's, and ISO Tank Containers. LIQUI-FIRE RXE, a blend of special petroleum, unique ethers, and emulsifiers, may be used as a presolve to soften hardened deposits prior to regular washing or it may be added to the wash as a booster. LIQUI-FIRE RXE penetrates and softens or dissolves deposits to facilitate their removal by subsequent washing. In pre-solve applications, LIQUI-FIRE RXE can be applied by spray, SVRU, or through recirculation systems.



Uses & Directions

Do not dilute with any other solvents. Use as is. For best results apply with a Presolve system from dome lids and cleanout or vent caps, without entering the tank. Recirculate with a pump system. For best results, seal up tank and allow to stand for 30 minutes after application. Especially effective for latex removal from Road Tankers & ISO containers with polymerized film in vapor space. Apply while tank is still hot from the wash and allow to stand for 30 minutes. LIQUI-FIRE RXE is a stellar performer for removing 4-ADPA. Special SOP available upon request for removal of this material.



Health Hazard Summary

Vapors can cause nausea, dizziness, nausea, stupor, vomiting, headache, and/or irritation to nose, throat, and respiratory system. Irritating to eyes and skin. Causes irritation to eyes. Prolonged exposure may irritate skin.



Specifications

Appearance Clear, Colorless Liquid
Odor Napthenic
pH N/A
Specific Gravity 0.97
Percent Active 100%
Flash Point 138° F
Dilution..... None - Use undiluted*
Foam N/A
Hardwater Tolerance N/A
Chlorinated Solvents None
Ammonia None
Phosphate None
Storage Stability Excellent**

** (emulsifiable)

* 1 yr under normal conditions

Package & Handling



55 gal drum JCRE8351

SDS



HMIS

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X