



TRIPLE PLAY

Floc Cleaner

TRIPLE PLAY was developed as a safe and effective polymer pre-solve for the tank washing industry. It is an emulsifiable blend of solvents and natural oils, works differently than most polymer pre-solves. Instead of causing the polymer to swell, TRIPLE PLAY encapsulates them, allowing their removal by a simple steam and hot-water flush. The solvents contained in this product are non-flammable and present little inhalation hazard. Contains nothing to damage, activate, or corrode stainless steel or other metals and it is safe to use through all types of equipment. Typical wash times are one hour and 10 minutes. SOP available upon request.

Use TRIPLE PLAY for removal of all types of water treatment polymers, especially where waste water minimization is desired.

Apply 5 gallons TRIPLE PLAY via presolve system, but low volume spinner is even better so as to coat entire tank uniformly. For multi-compartment tanks simply divide up the amount needed by the number of compartments, although an additional 20% may be needed for the extra bulkheads. Via rear discharge valve apply steam for 30 minutes. Close valve and remove steam line. Drop spinner into manway and apply 50 gallons hot water (usually around 30 seconds), then drain. Hot water flush again for 30 seconds. Cool tank and inspect.

SPECIFICATIONS FOR TRIPLE PLAY

Appearance.....	Clear, Amber Liquid
pH.....	N/A
Specific Gravity.....	0.83
Percent Active.....	100%
Flash Point.....	156° F
Dilution.....	None. Use undiluted
Foam.....	None
Hardwater Tolerance.....	N/A
Ammonia.....	None
Phosphate.....	None
Storage Stability.....	Excellent, 1 yr under normal conditions

HMIS RATINGS			
Health	1	Flammability	1
Phys Haz	0	Personal Protection	B

PACKAGING
55 gallon, #JBC7015

